

AMENDMENTS TO THE CLAIMS

The claims are amended as follows:

1. (Previously presented) A wireless communication terminal, comprising:
 - an operating unit;
 - reception field level detecting means for detecting a threshold field level of a received radio wave, including a determination of whether a the threshold field level has been detected;
 - a control unit for controlling the terminal;
 - a storage unit for storing said detected threshold field level;
 - a display unit and a speaker unit;
 - a plurality of wireless communication units for matching communication systems, including a first communication system that is currently selected, each of the plurality of wireless communication units respectively matching a different communication system; and
 - switch-over means for switching over from one to another of the wireless communication units, wherein:
 - if the terminal is busy with a call at a prescribed time, the terminal is scheduled to initiate exeution of detection of reception of a threshold field level of a second communication system after the call ends,
 - if the terminal is not busy at the prescribed time, the terminal initiates execution of detection of receptio of the threshold field level of the second communication system,
 - the terminal selects one of the communication systems on a basis of the reception of the threshold field level of a the first communication system ~~that is currently selected~~ and of a the threshold field level of ~~another~~ the second communication system, and
 - the terminal issues a notice signal when the second communication system has priority and communication with the second communication system is possible, the notice signal being at least either a display on the display unit or a sound emitted by the speaker unit.
2. (Previously presented) The wireless communication terminal, as set forth in Claim 1, wherein:

the terminal initiates execution of detection of the reception of the threshold field level of the second communication system when the reception of the threshold field level of the first communication system that is currently selected has become equal to or below a first threshold.

3. (Previously presented) The wireless communication terminal, as set forth in Claim 2, wherein:

the terminal selects the second communication system when the reception of the threshold field level of the first communication system is equal to or below a second threshold that is lower than the first threshold and communication with the second communication system is possible.

4. (Original) The wireless communication terminal, as set forth in Claim 2, wherein:

the terminal selects the second communication system when communication with the second communication system is possible.

5-6. (Canceled)

7. (Previously presented) The wireless communication terminal, as set forth in Claim 1, wherein:

the terminal selects the second communication system when the second communication system has priority and communication with the second communication system is possible.

8. (Canceled)

9. (Currently amended) The wireless communication terminal, as set forth in Claim 1, ~~wherein further comprising:~~

~~the terminal executes detection of the reception of the threshold field level of the first communication system~~ a timer for generating the prescribed time at prescribed intervals of time.

10. (Previously presented) The wireless communication terminal, as set forth in Claim 1, further comprising:

 a detection unit for detecting a prescribed operation of the terminal wherein:
 when the prescribed operation is done at the terminal, the terminal executes detection of the reception of the threshold field level of the second communication system.

11. (Original) The wireless communication terminal, as set forth in Claim 10, wherein:
 the terminal selects the second communication system when communication with the first communication system is impossible and communication with the second communication system is possible.

12. (Original) The wireless communication terminal, as set forth in Claim 11, wherein:
 the terminal determines possibility or impossibility of communication according to a prescribed threshold.

13. (Canceled)

14. (Original) The wireless communication terminal, as set forth in Claim 10, wherein:
 the terminal selects the second communication system when the second communication system has priority and communication with the second communication system is possible.

15. (Canceled)

16. (Original) The wireless communication terminal, as set forth in Claim 10, wherein:
 the terminal is foldable.

17. (Previously presented) The wireless communication terminal, as set forth in Claim 16, wherein:
 the prescribed operation comprises an operation to unfold the terminal.

18. (Previously presented) The wireless communication terminal, as set forth in Claim 10, wherein:

the prescribed operation comprises an operation on the operating unit.

19. (Currently amended) The wireless communication terminal, as set forth in Claim 10, further provided with:

a specific key, ~~wherein:~~ wherein the prescribed operation comprises an operation on the specific key.

20. (Currently amended) A control method for a wireless communication terminal permitting use of a plurality of communication systems, including a first communication system that is currently selected, said method comprising:

~~initiating~~ if the terminal is busy with a call at a prescribed time, scheduling to initiate execution of a detection of a reception of a threshold field level of a second communication system ~~when the reception field level of a first communication system that is currently selected is at or below a prescribed threshold, and after the call ends;~~

if the terminal is not busy at the prescribed time, initiating execution of detection of reception of the threshold field level of the second communication system; and

selecting either communication system on a basis of the reception of the threshold field levels of said two communication systems, ~~wherein:~~

~~the terminal initiates an execution of the detection of the reception of the field level of the second communication system when the reception of the threshold field level of the first communication system that is currently selected has become equal to or below a first threshold, and~~

~~the terminal selects the second communication system when the reception of the threshold field level of the first communication system is equal to or below a second threshold that is lower than the first threshold and communication with the second communication system is possible.~~

21. (Currently amended) The control method, as set forth in Claim 20, ~~wherein:~~ further comprising:

issuing a notice signal ~~is issued~~ when the second communication system has priority

and communication with the second communication system is possible.

22. (Currently amended) The control method, as set forth in Claim 20, ~~wherein:~~ further comprising:

selecting the second communication system ~~is selected~~ when the second communication system has priority and communication with the second communication system is possible.

23. (Currently amended) A ~~The~~ control method ~~for a wireless communication terminal permitting use of a plurality of communication systems~~ as set forth in claim 20, further comprising:

detecting whether or not a prescribed operation has been done on the terminal;

detecting, when the prescribed operation has been done, a reception of the threshold field level of ~~another~~ the second communication system ~~than a first communication system that is selected then;~~ and

selecting either communication system on a basis of the reception of the threshold field levels of said two communication systems.

24. (Currently amended) The control method, as set forth in Claim 23, wherein:

the terminal is foldable, and said prescribed operation comprises an operation to unfold the terminal.

25. (Currently amended) The control method, as set forth in Claim 23, wherein:

the prescribed operation comprises an operation on the operating unit of the terminal.

26. (Currently amended) The control method, as set forth in Claim 23, wherein:

the terminal is provided with a specific key, and said prescribed operation comprises an operation on the specific key.

27. (Currently amended) The control method, as set forth in Claim 23, ~~wherein:~~ further comprising:

issuing a notice signal ~~is issued~~ when the second communication system has priority

and communication with the second communication system is possible.

28. (Currently amended) The control method, as set forth in Claim 23, ~~wherein:~~ further comprising:

selecting the second communication system ~~is selected~~ when the second communication system has priority and communication with the second communication system is possible.

29. (New) The control method, as set forth in claim 20, further comprising:

initiating execution of detection of the reception of the threshold field level of the second communication system when the reception of the threshold field level of the first communication system has become equal to or below a first threshold.

30. (New) The control method, as set forth in claim 29, further comprising:

selecting the second communication system when the reception of the threshold field level of the first communication system is equal to or below a second threshold that is lower than the first threshold and communication with the second communication system is possible.